

# CLARKE ACCESS CONTROL PRODUCTS

## FENCE LINE TURNSTILE



All fence line turnstiles feature a 90-degree or 120-degree rotor with straight or hooped push bars. They are fully weather resistant and will operate in an external environment. Electrically controlled entry/exit or free wheel option. Available with fail locked or unlocked solenoids to conform to security or fire safety requirements.



Model	Description	Type Number
<i>Sarum</i>	90° Full Height Rotor with Straight Push Bars	491/S/B Single Walkway
		491/D/B Double Walkway
<i>Bourne</i>	90° Full Height Rotor with Hooped Push Bars	491/S/H Single Walkway
		491/D/H Double Walkway
<i>Salisbury</i>	120° Full Height Rotor with Straight Push Bars	474/S/B Single Walkway
		474/D/B Double Walkway
<i>Wilton</i>	120° Full Height Rotor with Hooped Push Bars	474/S/H Single Walkway
		474/D/H Double Walkway

12v DC Logic Control is integral with the 230v AC mains supplied power supply unit. This is normally located within the turnstile canopy. Cables to this are routed internally via vertical sections of the turnstile frame. The logic control readily accepts voltage free contacts from most access control devices, e.g., card readers, digi pads, push buttons.

Designed and Manufactured by  
**CLARKE INSTRUMENTS LIMITED**  
 Distloc House, Old Sarum Airfield,  
 The Portway, Salisbury, Wiltshire. SP4 6DZ.  
 TEL: 01722 323451 FAX: 01722 335154  
 Web: [www.clarke-inst.com](http://www.clarke-inst.com)  
 E-mail: [sales@clarke-inst.com](mailto:sales@clarke-inst.com)

Supplied by:



C.I.L. products comply with EMC Directives of EEC  
 Certificate Number FM12702  
 BS EN ISO9001:2000